







Accessories

Components & Sizes

	Components	Materials	Sizes												
<div>Nozzle Strainers</div> <div></div>	Optional strainer to fit BJ and CW nozzles. All strainers equipped with 316 stainless steel screens of various mesh sizes.	316 stainless steel	US Mesh Sizes: 50 (297 μm) (S201) 100 (149 μm) (S202) 200 (74 μm) (S203) 400 (37 μm) (S204)												
<div>Reducing Bushings</div> <div></div>	BETE nozzles are often installed in pipe sizes larger than their connection. These bushings will adapt BETE nozzles to existing piping.	316 stainless steel nickel alloy C-276 nickel alloy 625 PVC PTFE	Bushing Sizes: 1/4 x 1/8 3/8 x 1/8, 1/4 1/2 x 1/8, 1/4, 3/8 1 x 1/4, 3/8, 1/2, 3/4 1-1/2 x 1/4, 1/2, 1 2 x 1/2, 1												
<div>Y-Type Line Strainers</div> <div></div>	BETE recommends the use of strainers to minimize clogging. The 1/4" and 3/8" strainers are equipped with 0.25mm-mesh screens, while 1/2" - 2" strainers come with 0.20mm-mesh screens. Screens with mesh sizes of 0.05, 0.06, 0.13 and 0.15mm available by special order. Screens are easily removed for cleaning. 10 bar rating.	Bronze body with heavy-duty stainless steel wire mesh.	Strainer Sizes: 1/4, 3/8, 1/2, 3/4, 1, 1-1/2, 2 <table><tr><th>Mesh Sizes</th><th>Screen Opening</th></tr><tr><td>0.25 mm</td><td>0.13 mm</td></tr><tr><td>0.20 mm</td><td>0.18 mm</td></tr><tr><td>0.13 mm</td><td>0.28 mm</td></tr><tr><td>0.06 mm</td><td>0.71 mm</td></tr><tr><td>0.05 mm</td><td>0.86 mm</td></tr></table>	Mesh Sizes	Screen Opening	0.25 mm	0.13 mm	0.20 mm	0.18 mm	0.13 mm	0.28 mm	0.06 mm	0.71 mm	0.05 mm	0.86 mm
Mesh Sizes	Screen Opening														
0.25 mm	0.13 mm														
0.20 mm	0.18 mm														
0.13 mm	0.28 mm														
0.06 mm	0.71 mm														
0.05 mm	0.86 mm														
<div>Adapters and Couplings</div> <div></div>	Reducing couplings, socket adapters, elbows, and various other fittings are available to meet specific applications.	Wide range of materials available.	Sizes available as required												
<div>Flanges</div> <div></div>	Used to attach nozzles too large to be threaded. 150# rating, ANSI standard; 300# and specific ratings also available.	316 stainless steel nickel alloy C-276 nickel alloy 625 PVC PTFE FRP	Flange Sizes: 2" - 12" DN 50 - DN 300												
<div>Manifolds</div> <div></div>	Used to cluster many nozzles into a small physical space	Wide range of materials available	Standard Sizes <table><tr><th>Inlet</th><th>Outlets</th></tr><tr><td>1/2"</td><td>x (7) 3/8"-24 UNF</td></tr><tr><td>3/4"</td><td>x (6) 1/4" or 3/8"</td></tr><tr><td>1"</td><td>x (6) 3/8" or 1/2"</td></tr></table>	Inlet	Outlets	1/2"	x (7) 3/8"-24 UNF	3/4"	x (6) 1/4" or 3/8"	1"	x (6) 3/8" or 1/2"				
Inlet	Outlets														
1/2"	x (7) 3/8"-24 UNF														
3/4"	x (6) 1/4" or 3/8"														
1"	x (6) 3/8" or 1/2"														

SPECIAL PURPOSE

CALL 413-772-0846
Call for the name of your nearest BETE representative.