



VGYZ.EX5210
Nozzles, Spray Type, Fixed

[Page Bottom](#)

Nozzles, Spray Type, Fixed

[See General Information for Nozzles, Spray Type, Fixed](#)

BETE FOG NOZZLE INC

50 GREENFIELD ST
GREENFIELD, MA 01301-1378 USA

EX5210

Model	Discharge Angle Deg	Discharge Coefficient K
3/8FF187	145	0.949
3/8FF196	145	1.11
3/8FF209	145	1.19
3/8FF218	145	1.26
3/8FF221	145	1.42
1/2N1	90	0.95
1/2N1W	120	0.95
1/2N2	90	1.68
1/2N2W	120	1.68
1/2N3	90	2.61
1/2N3W	120	2.61
1/2N4	90	3.81
1/2N4W	120	3.81

Model	Discharge Angle Deg	Discharge Coefficient K
1/2N5	90	5.22
1/2N5W	120	5.22
1/2N6	90	6.64
1/2N6W	120	6.64
1N6	90	6.64
1N6W	120	6.64
1N7	90	10.59
1N7W	120	10.59
1-1/2N8	90	15.02
1-1/2N8W	120	15.02
1-1/2N9	90	20.4
1-1/2N9W	120	20.4
1-1/2N10	90	26.72
1-1/2N10W	120	26.72

Last Updated on 2016-06-20

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".